


Braided Well Services Strands - Formed.

A range of well servicing products in high Carbon, Stainless and special Alloy Steels.

Continuous lengths on drums-Tested & Certified to DIN.50049.3.1.BS EN 10204-2004.



Strand Diameter		Rec. Flow Tube Diameter Measure Line to Confirm		Approx Weight	Minimum Breaking Load			Minimum Pulley dia
Ins	mm	Ins	mm	Lbs/1000ft	Lbs Galv	Lbs 316	Lbs GD31MO	Ins*
3/16"	4.76	0.196	4.98	85	6170	4940	5060	12*
7/32"	5.56	0.228	5.79	110	8370	6500	6110	14*
1/4"	6.35	0.263	6.68	150	11200	8640	8700	16*
5/16"	7.94	0.330	8.38	235	17550	13560	134700	20*

Material	H2S & CO2	Chloride, Brine, Etc	H2S + CO2 + Chlorides
Galvanised	O.K at very low concentrations. Use of Inhibitors cab benefit	Not badly affected but wash and oil after use	Not Suitable
Grade 316 Stainless	O.K in concentrations up to 30%	Venerable in concentrations in excess of 3%	O.K if CO2 is less than 30%, chlorides don't exceed 3% and no H2S present
Alloy Steel	O.K at any concentration	O.K at any concentration	O.K at any concentration